

Mod. D/G2

INDUSTRIAL VACUUM CLEANER FOR DUST, LIQUID AND SOLID MATERIAL



MODEL		DG 2
Tension	Volts HZ	400 3~ 50/60
Power	KW / Hp	5,5 / 7,5
Max. Vacuum rate	mm.H ₂ O	5000
Limit for continuous duty	mm.H ₂ O	3000
Max. Air flow rate	M ³ /h	500
Filter surface (pocket filter)	Cm ²	49.000
Filter efficiency	CAT BIA Micron	L > 3
Air load on filter	M ³ /M ² /h	102
Capacity	Lt.	100
Suction inlet	∅	80
Noise level	Db(A)	71
Protection	IP	55
Dimensions	cm.	63 x 123
Height	cm.	170
Weight	cm.	165

Suction unit

The suction is provided by a **suction unit of the side channel blower type**, with **direct coupling** between the fan and the motor shaft and **no transmission system**. It is thus **completely maintenance free, fit for round-the-clock 24 hours duty, very silent** and provides **outstanding suction performances; a safety switch cuts off the motor in case of overheating**. A safety **cartridge filter**, placed between the motor and the main filter, **protects the motor from contact with dust** in case of dust accidentally passing through the main filter; a **vacuum indicator** enables **constant checking of the suction performance**, and **detecting possible clogging of the filter**. A **diffuser filter** reduces the speed and noise of the air on the exhaust outlet.

Filter unit

The **polyester star filter**, placed and protected inside the steel filter chamber, **provides a filter surface of 49.000 cm²**, and high **filtration efficiency (class L, 3 micron)**. A **manual filter shaker** enables the user to **clean the filter efficiently**, by a vertical shaking movement, so as to detach most of the dust and **maintain the filter clean**, in order to **increase its life and maintain the suction performance** of the machine. The **tangential aluminium die-cast suction inlet**, placed below the filter, makes it **possible to vacuum at the same time dust, solid and liquid material** (the latter only within the capacity of the container), with **no need to change or take out the filter**. A **cyclone** welded inside the filter chamber conveys most of the dust directly in the container, and protects the filter from cutting or tearing.

Collection unit

The vacuumed material is placed inside a **drop-down bin mounted on wheels** (100 litres capacity), which makes it possible to **dispose easily and safely of the sucked material**, if need be collecting it directly into a plastic bag.

The vacuum is mounted on a **sturdy steel chassis** with two pivoting wheels, one of which with brakes; **all metal parts of the vacuum are epoxy painted**.



Options*

Application	Code	Description
Sticky dust and material	PTFE	PTFE treated pocket filter (reduces the adherence of the dust on the filter)
High temperature dust and material	NOMEX	Nomex flame proof filter, resistant up to 250° C temperatures
Dust and material subject to accumulate static electricity	ANT	Antistatic pocket filter
Dust and material subject to accumulate static electricity	MT	Total electrical grounding of metal parts
Fine dust subject to accumulate static electricity	ANT/C	Antistatic pocket filter, 1 micron efficiency
Very fine dust	A	Absolute HEPA filter (BIA certified) with efficiency 99,995% particle size 0,18 µm standard EN 1822
Fine dust	C (CLASS M)	1 micron pocket filter, pressure relief valve, for the suction of fine dust of class "M"
Very fine and / or toxic dust	A/C (CLASS H)	1 micron pocket filter, absolute HEPA filter (BIA certified) with efficiency 99,995% particle size 0,18 µm standard EN 1822, for the suction of very fine and toxic dust of class "H".
Explosive dust	ATEX	Explosion proof conformity according to European ATEX standards, for zone 22 (rare presence of explosive dust)
Big quantities of fine dust	PNEUMATIC	2 Cartridges with automatic reverse pulse pneumatic cleaning
Big quantities of liquid	FLOTTEUR	Floating device to stop the suction when container is full
Suction of explosive material or service in ATEX rated Zones	ATEX	Explosion proof certificate Zone 22 and Zone 21
Corrosive dust and material	X	Stainless steel container AISI304
Corrosive dust and material	XX	Stainless steel container and filter chamber AISI304
Highly corrosive dust and material	XXX	Complete body (Chassis, container and filter chamber) in stainless steel AISI304

* Different combinations of the above options are possible (e.g. ACX , vacuum with Absolute filter, 1 micron pocket filter and stainless steel container)